


A New Isolation Building Facility Washoe Park Trout Hatchery


FWP Project #7153604 Re-bid August 2017


ABBREVIATIONS	SYMBOLS	INDEX OF DRAWINGS	OWNER INFORMATION	Beauci 113 W Misso
Aug. Aug.	OFFICE -	A-1: COVER SHEET / CODE AND PROJECT INFORMATION A-2: SITE PLAN A-3: FOUNDATION, FLOOR AND ROOF FRAMING PLANS A-4: EXTERIOR ELEVATIONS / TYPICAL WALL SECTION A-5: BUILDING SECTIONS / DETAILS ME: COVER SHEET AND GENERAL NOTES M-1: HVAC PLAN M-2: PLUMBING PLAN M-3: EQUIPMENT SCHEDULES AND DETAILS E-1: LIGHTING AND POWER FLOOR PLAN E-2: ELECTRICAL SCHEDULES PROJECT DATA BUILDING USE: CPRISON CONTROL OF PLAN E-2: ELECTRICAL SCHEDULES PROJECT DATA PROJECT DATA	OWNER: State of Montana Fish Mildlife and Parks I420 East 6th Ave Helena, MT 54601-3811 PROJECT ADDRESS: 600 Fennsylvania Street Aanaconda, Montana 59111 LEGAL DESCRIPTION: 503, T04 N, RIL M, ACRES 4,36, TR IN NM4 Geacade:30-1285-03-2-26-01-0000	Mechan Dawes 48 Hibh Helena, Electric Dawes 48 Hibh Helena, Plumbir Dawes 48 Hibh Helena, Geotec Robert P.O. Bo Helena, Date: 8 Project Drawn Checke Revisio


WRN Architects


Architecture: Planning: Consulting











PLUMBING LINE KEY
——3" SAN ——— SANITARY SEWER ABOVE GRADE
3" SAN SANITARY SEWER BELOW GRADE
—— 2" V ——— SEWER VENT ABOVE GRADE
2" V SEWER VENT BELOW GRADE
—_3" G-SAN —— GREASE SANITARY SEWER ABOVE GRADE
3" G-SAN GREASE SANITARY SEWER BELOW GRADE
——1" DCW —— DOMESTIC COLD WATER UNDER ABOVE GRADE
1" DCW DOMESTIC COLD WATER BELOW GRADE
——1" DHW —— DOMESTIC HOT WATER ABOVE GRADE
——1" DHWR —— DOMESTIC HOT WATER RECIRCULATED
——1" NG ——— NATURAL GAS ABOVE GRADE
1" NG NATURAL GAS BELOW GRADE
——1" LP ——— LP GAS ABOVE GRADE
1"LPLP GAS BELOW GRADE

110	AC DUCTING KEY
12"X10" SA	RECTANGULAR SUPPLY AIR DUCT
12"X10" RA	RECTANGULAR RETURN AIR DUCT
12"X10" EX	RECTANGULAR EXHAUST DUCT
12"X10" OA	RECTANGULAR OUTSIDE AIR DUCT
12"X10" TA	RECTANGULAR TRANSFER AIR DUCT
12"X10" GE	RECTANGULAR GREASE EXHAUST DUCT
12"X10" MP	RECTANGULAR MEDIUM PRESSURE DUCT
12"X10"	RECTANGULAR DUCT (NON-SPECIFIC-REFER TO SYSTEM
12"X10"	SPECIFICALLY LINED RECTANGULAR DUCT
8"Ø	ROUND DUCT-REFER TO SYSTEM SERVED
8"Ø	ROUND LINED OR DOUBLE WALL DUCT

	HVAC CONTROL SYMBOLS								
SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION						
	GATE, BALL, OR FUEL SOV VALVE	T	ROOM OR ZONE THERMOSTAT						
	GLOBE VALVE	T	DUCT THERMOSTAT						
—————————————————————————————————————	GAS COCK	Į.	THERMOMETER WITH WELL						
<u> </u>	SOLENOID VALVE	⊘	PRESSURE GAGE WITH SHUTOFF						
	CONTROL VALVE , 2-WAY	*/*/*/	DAMPER						
PRV PRV	PRESSURE REDUCING VALVE	SD	SMOKE DETECTOR						
	CHECK VALVE	F	FLOW SWITCH						
	PLUG VALVE	F	FLOW SWITCH						
──	EXPANSION VALVE	FS	FIRE SAFETY SWITCH						
*	PRESS./TEMP. RELIEF VALVE	\mathbb{H}	HUMIDISTAT, ROOM						
	CONTROL VALVE , 3-WAY	Н	HUMIDISTAT, DUCT						
	STRAINER, CAST IRON OR BRONZE	Р	PRESSURE SWITCH						
— + ¼ 	STRAINER WITH BLOW DOWN & PLUG	MD	DAMPER ACTUATOR						
, ∓	1/4 TURN BOILER DRAIN W/CAP	Fs	FLOW SWITCH						
	NG OR LP EQUIPMENT REGULATOR	Р п	TEMPERATURE TRANSMITTER (SENSOR)						
	FLEXIBLE PIPE CONNECTOR	PT/PS	PRESSURE TRANSMITTER OR SWITCH						
<u> </u>	STEAM TRAP	SP D	DIFFERENTIAL PRESSURE CONTROLLER						
M	MOTOR		AUTO AIR VENT, EXTEND TO DRAIN						
	PUMP	LMBV_L	MANUAL BALANCING VALVE						
	CENTRIFUGAL FAN	LABV_L	AUTOMATIC BALANCING VALVE						

PLUMBING/PIPING SYMBOLS								
SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION					
	GATE, BALL, BUTTERFLY, OR FUEL SOV VALVE	——————————————————————————————————————	UNION, THREADED OR FLANGED					
	GLOBE VALVE	F SA	WATER HAMMER ARRESTOR					
	GAS COCK		FLOOR DRAIN					
	PLUG VALVE	•	FLOOR SINK					
<u> </u>	SOLENOID VALVE	0	FLOOR CLEANOUT, INT. OR EXT.					
PRV PRV	PRESSURE REDUCING VALVE	CO	WALL CLEANOUT					
	CHECK VALVE	, T	1/4 TURN BOILER DRAIN W/CAP					
*	PRESS./TEMP. RELIEF VALVE	 +	HOSE BIBB, INTERIOR OR EXTERIOR					
-MMM	RPP BACKFLOW PREVENTOR	Д н м	90 DEGREE ELBOW (UP, DOWN, PLAN)					
-WЙW	DOUBLE CHECK BACKFLOW PREV.	ю н	TEE FITTING (UP, DOWN, PLAN)					
	WATER METER	Й	WYE (PLAN)					
<u> </u>	PRESSURE REDUCING VALVE	Y ^l	COMBINATION WYE & 1/8 BEND					
Q	THERMOMETER WITH WELL	<u> </u>	WYE (VERTICAL) WITH 1/4 BEND					
 	PRESSURE GAGE WITH SHUTOFF	ζ 1	LONG RADIUS SAN. SEWER FITTING					
Р	PRESSURE SWITCH	LMBVL	MANUAL BALANCING VALVE					
	PUMP		DIRECTION OF FLOW					

DUCTWORK SYMBOLS KEY SECTION THROUGH RETURN OR EXHAUST AIR SECTION THROUGH SUPPLY OR OUTSIDE AIR DUCT SUPPLY, RETURN, EXHAUST, OR OUTSIDE AIR DUCT ACCESS DOOR (BOTTOM OR SIDE) ACOUSTICALLY LINED DUCT DAMPER, FIRE _____ VD DAMPER, MANUAL VOLUME _____ INCLINED DROP IN DIRECTION OF ARROW INCLINED RISE IN DIRECTION OF ARROW TRANSITION, RECTANGULAR TO ROUND FLEXIBLE DUCT TRANSITION OR OFFSETTING TRANSITION TRANSITION. RECTANGULAR HIGH EFFICIENCY TAKEOFF WITH DAMPER CEILING SUPPLY AIR DIFFUSER ## SIDEWALL SUPPLY AIR REGISTER ## ELBOW TURNED DOWN ELBOW TURNED UP ELBOW, RADIUS TYPE ELBOW, SQUARE OR RECTANGULAR TYPE WITH 22 GA SINGLE TURNING VANES RETURN OR EXHAUST AIR DUCT CEILING RETURN AIR REGISTER ## SIDEWALL RETURN AIR REGISTER ## -OPEN END DUCT FLEXIBLE CONNECTION

ELECTRICAL HARDWARE

CONDUIT & RACEWA	YS SHALL BE CONCEALED AND APPROVED FOR USE AND LOCATION.
DRY LOCATIONS UNDERGROUND FLEXIBLE CONDUIT LIQUID	- GRC, IMC, EMT GRC, PVC ALLOWED ONLY FOR CONNECTION OF EQUIPMENT AND LIMITED TO LENGTHS OF SIX FEET. GALVANIZED, - TIGHT. MC OR AC ALLOWED WHEN PROTECTED PROVIDE SEPARATE EQUIPMENT GROUNDING CONDUCTOR IN CONDUIT.
NM-B CABLE	- NOT ALLOWED.
JUNCTION AND PULL DRY LOCATIONS WET LOCATIONS SIZE PER NEC.	- STEEL WITH COVERS.

COUPLINGS AND CONNECTORS: IMC - THREADED

EMT - DRY-COMPRESSION OR SET SCREW, BOTH OF STEEL, WET-RAIN TIGHT PVC - CEMENT JOINT TYPE INDENTER TYPE CONNECTORS PROHIBITED.

CABELING DEVICES AND PLATES: HUBBELL #CR20 SERIES, 20 AMP (OR APPROVED EQUAL) GFCI OUTLETS - HUBBELL #GF20 SERIES, 20 AMP (OR APPROVED EQUAL) - HUBBELL #CS120 SERIES (OR APPROVED EQUAL) AC SWITCHES FOR 3 WAY OR 4 WAY USE EQUIVALENT **DEVICE COLOR** - COORDINATE COLOR W/ OWNER OR ARCHITECT - NYLON. COORDINATE COLOR W/ OWNER OR ARCHITECT OCCUPANCY SENSORS - HUBBELL #WS120W (OR APPROVED EQUAL)

ANCHORS: HOLLOW MASONRY - TOGGLE BOLT. SOLID MASONRY - EXPANSION BOLT. - METAL MACHINE SCREWS, BOLTS. STEEL WOOD WOOD SCREWS.

P.C. PLUMBING CONTRACTOR M.C. MECHANICAL CONTRACTOR E.C. ELECTRICAL CONTRACTOR

COMPLY WITH ADA REQUIREMENT.

MOUNTING HEIGHTS DESCRIPTION HEIGHT UNLESS OTHERWISE NOTED THERMOSTAT, CONTROLLER WALL SWITCH/ OCCUPANCY SENSOR CONVENIENCE OUTLET WALL SWITCHES TELEPHONE/DATA/TV OUTLETS FIRE ALARM MANUAL STATION FIRE ALARM HORNS & STROBES 90" A.F.F.-6" BELOW CEILING EXIT SIGN CENTER, 4" ABOVE DOOR MANUAL MOTOR STARTER SWITCH PANELBOARDS, CABINETS

MOUNTING HEIGHTS TO TOP OF BOX AND ABOVE FINISHED FLOOR GRADE

UNLESS NOTED OTHERWISE. MATCH EXISTING MOUNTING HEIGHTS WHICH

BASIC MECHANICAL/ELECTRICAL/PLUMBING REQUIREMENTS

FURNISH ALL LABOR AND MATERIALS AND PERFORM ALL OPERATIONS NECESSARY FOR THE INSTALLATION OF COMPLETE AND OPERATING MECHANICAL/ELECTRICAL SYSTEMS SUBJECT TO THE CONDITIONS OF THE CONTRACT. PROVIDE SATISFACTORY OPERATION OF ALL EQUIPMENT AND CONTROLS TO THE ARCHITECT/ENGINEER UPON REQUEST.

ALL MATERIALS SHALL BE NEW. SUBSTITUTIONS SHALL BE APPROVED BY OWNER AND/OR ENGINEER.

VISIT THE PREMISES BEFORE SUBMITTING BID AS NO CHANGE ORDERS WILL BE ALLOWED FOR LACK OF KNOWLEDGE OF EXISTING

COORDINATE AND ORDER THE PROGRESS OF WORK TO CONFORM TO THE PROJECT SCHEDULE AND THE PROGRESS OF THE WORK OF THE OTHER TRADES.

MECHANICAL/ELECTRICAL DRAWINGS ARE DIAGRAMMATIC AND BECAUSE OF THE SMALL SCALE, IT IS NOT POSSIBLE TO INDICATE EVERY REQUIRED OFFSET, FITTING, ETC. VERIFY ALL SPACE REQUIREMENTS, COORDINATING WITH OTHER TRADES, AND INSTALL THE SYSTEMS IN THE SPACE PROVIDED WITHOUT EXTRA CHARGES TO THE OWNER.

PERFORM WORK IN ACCORDANCE WITH GOOD COMMERCIAL PRACTICE. THE GOOD APPEARANCE OF THE FINISHED WORK SHALL BE OF EQUAL IMPORTANCE WITH ITS MECHANICAL/ELECTRICAL EFFICIENCY AND INTENT. THE OWNER MAY REJECT WORK IF WORKMANSHIP AND APPEARANCE ARE NOT SATISFACTORY.

INSTALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH THE MANUFACTURERS' RECOMMENDATIONS UNLESS SPECIFICALLY INDICATED OTHERWISE, OR WHERE LOCAL CODES OR REGULATIONS TAKE PRECEDENCE.

COMPLY WITH STATE AND LOCAL CODE REQUIREMENTS AND ORDINANCES. COMPLY WITH REQUIREMENTS OF THE UTILITY COMPANIES. IN THE CASE OF DIFFERENCES BETWEEN THESE REQUIREMENTS AND ORDINANCES, THE MOST STRINGENT SHALL GOVERN. CALL FOR INSPECTIONS REQUIRED BY LOCAL BUILDING INSPECTION AUTHORITY.

PLANS AND SPECIFICATIONS GO HAND IN HAND. WHAT IS REQUIRED IN ONE IS REQUIRED IN BOTH. WHERE CONFLICTS BETWEEN SPECIFICATIONS AND PLANS EXIST, THE MOST STRINGENT REQUIREMENTS SHALL APPLY.

MECHANICAL/ELECTRICAL PLANS SUPERCEDE ARCHITECTURAL PLANS. BACKGROUND FLOOR PLANS USED FOR MECHANICAL/ELECTRICAL DRAWINGS MAY SHOW DIFFERENT THAN THE FINAL ARCHITECTURAL LAYOUT. REFER TO ARCHITECTURAL DRAWINGS FOR ACTUAL DIMENSIONS AND LAYOUT PLACEMENTS FOR SPACE CONDITIONS.

MECHANICAL AND ELECTRICAL DETAILS MAY OR MAY NOT BE DIRECTLY REFERENCED. ALL DETAILS SHOWN ARE TO BE USED FOR BASIS OF INSTALLATION IN ALL CASES, IN COORDINATED EFFORT WITH MANUFACTURERS INSTALLATION RECOMMENDATIONS.

MECHANICAL SHEETS ARE NOT INTENDED TO SPECIFICALLY BE TRADE SPECIFIC TO MECHANICAL INSTALLATION WORK. ELECTRICAL SHEETS ARE NOT INTENDED TO SPECIFICALLY BE TRADE SPECIFIC TO ELECTRICAL INSTALLATION WORK. ALL MECHANICAL AND ELECTRICAL TRADES ARE RESPONSIBLE FOR FAMILIARIZING THEMSELVES AND INCLUDING A COMPLETE PACKAGE WITHIN THEIR OFFER FOR A COMPLETE SYSTEM.

AT COMPLETION OF WORK, DELIVER COMPLETED PROJECT RECORD DOCUMENTS MARKED WITH FIELD CHANGES TO OWNER.

PROVIDE A WRITTEN WARRANTY TO THE OWNER COVERING THE DEFECTIVE MATERIALS, EQUIPMENT AND WORKMANSHIP FOR A PERIOD OF 1 YEAR AFTER DATE OF ACCEPTANCE.

CLEAN EXPOSED SURFACES OF LIGHT FIXTURES. SWITCHGEAR. FURNACES, HOT WATER HEATERS, PLUMBING FIXTURES AND OTHER EXPOSED ITEMS OF GREASE, DIRT OR OTHER FOREIGN MATERIAL. REMOVE RUBBISH AND DEBRIS RESULTING FROM THE OPERATIONS AND LEAVE EQUIPMENT SPACES CLEAN AND READY FOR USE.

MAINTAIN ALL CEILING, FLOOR AND WALL FIRE AND SMOKE PROTECTION RATINGS. SEAL ALL CONDUIT AND ENCLOSURE PENETRATIONS TO COMPLY WITH UL ASSEMBLY AND BUILDING CODE REQUIREMENTS. ALL SEALANTS AND CONSTRUCTIONS SHALL BE APPROVED BY OWNER PRIOR TO APPLICATION. ALL OPENINGS SHALL BE SEALED DAILY.

CONTRACT DRAWINGS FOR MECHANICAL/ELECTRICAL WORK ARE IN PART DIAGRAMMATIC, INTENDED TO CONVEY THE SCOPE OF WORK AND INDICATE GENERAL ARRANGEMENT OF EQUIPMENT, CONDUITS, AND APPROXIMATE SIZES AND LOCATIONS OF EQUIPMENT AND OUTLETS. MECHANICAL/ELECTRICAL TRADES SHALL FOLLOW THESE DRAWINGS IN LAYING OUT THEIR WORK, CONSULT GENERAL CONSTRUCTION DRAWINGS TO FAMILIARIZE THEMSELVES WITH ALL CONDITIONS AFFECTING THEIR WORK, AND SHALL VERIFY SPACES IN WHICH THEIR WORK WILL BE INSTALLED. COORDINATE WORK WITH OTHER TRADES AND AS PROJECT CONDITIONS REASONABLY REQUIRE WITHOUT EXTRA COSTS TO OWNER.

RACEWAYS SHALL BE LEFT WITH 30% FREE SPACE FOR FUTURE

SHARING OF NEUTRALS BETWEEN PHASES SHALL NOT BE

SEPARATE GROUNDING CONDUCTORS SHALL BE PROVIDED IN ALL

CONDUCTORS SHALL BE COPPER. COLOR CODING SHALL BE NEC APPROVED AND AT MINIMUM SHALL BE AS FOLLOWS: 120/208 VOLT-BLACK, RED, BLUE FOR PHASE CONDUCTORS, WHITE FOR NEUTRAL CONDUCTORS, 277/480 VOLT-BROWN, ORANGE. YELLOW FOR PHASE CONDUCTORS, GRAY FOR NEUTRAL CONDUCTORS. GROUNDING CONDUCTORS SHALL BE GREEN.

ELECTRICAL SYSTEMS SHALL COMPLY WITH 2014 NATIONAL ELECTRICAL CODE AND BE INSTALLED BY LICENSED CONTRACTORS. LIGHTING SHALL COMPLY WITH THE 2012 IECC.

ALL DUCTWORK DIMENSIONS, AS SHOWN ON THE DRAWINGS, ARE INTERNAL CLEAR DIMENSIONS AND DUCT SIZE SHALL BE INCREASED TO COMPENSATE FOR DUCT LINING THICKNESS.

PROVIDE ALL 90 DEGREE SQUARE ELBOWS WITH SINGLE RADIUS TURNING VANES UNLESS OTHERWISE INDICATED.

COORDINATE DIFFUSER, REGISTER, AND GRILLE LOCATIONS WITH ARCHITECTURAL REFLECTED CEILING PLANS, LIGHTING, AND OTHER CEILING ITEMS AND MAKE DUCT MODIFICATIONS TO SUIT.

AT CONTRATORS OPTION, FLEXIBLE DUCT MAY BE USED TO CONNECT SUPPLY REGISTERS AND DIFFUSERS ON THIS PROJECT ONLY. RUNS OF FLEXIBLE DUCT SHALL NOT EXCEED 5 FEET, UNLESS SPECIFICALLY SHOWN ON DRAWING.

INVOLVED. OFFSETS IN DUCTS, INCLUDING DIVIDED DUCTS AND TRANSITIONS AROUND OBSTRUCTIONS, SHALL BE PROVIDED AT NO ADDITIONAL COST TO THE OWNER.

ALL DUCTWORK SHALL BE COORDINATED WITH ALL TRADES


MECHANICAL SYSTEMS SHALL COMPLY WITH INTERNATIONAL MECHANICAL CODE VER 2012 AND INTERNATIONAL ENERGY CODE


PLUMBING/PIPING SYSTEMS SHALL COMPLY WITH INTERNATIONAL FUEL GAS CODE VER 2012 AND UNIFORM PLUMBING CODE VER 2012.


LOCATION OF UNDERGROUND UTILITIES ARE APPROXIMATE. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO DETERMINE EXACT


REGULATORY AND CODE REQUIREMENTS: APPLY FOR AND PAY FOR ALL PERMITS, FEES, LICENSES AND INSPECTIONS, ALL WORK IS SUBJECT TO APPROVAL BY THE CODE OFFICIAL AND ENGINEER. ALL CORRECTIONS SHALL BE MADE WITHOUT EXTRA COSTS TO OWNER.


EL	ECTRICAL LEGEND
SYMBOL	DESCRIPTION
φ	DUPLEX OUTLET, STANDARD HEIGHT/COORD ELEV.
₩	DOUBLE DUPLEX RECEPTACLE
42" GFI	GROUND FAULT CIRCUIT INTERRUPTER OUTLET
P	220 VOLT RECEPTACLE
₩P	WEATHER PROOF OUTLET WITH COVER W/ GFCI
42" 🌓	DUPLEX OUTLET, ELEVATION CALLOUT
00	JUNCTION BOX
	BRANCH CIRCUIT PANEL
ᇝ	FUSED DISCONNECT SWITCH
⊠j	COMBINATION MOTOR STARTER / DISCONNECT
×	STARTER/CONTACTOR
Ū	THERMOSTAT
$S_{_{\!\scriptscriptstyle T}}$	SWITCH, WIND UP TIMER
S _p	SWITCH, PILOT DUTY/CONTROL LEG CONTACTOR
S	SWITCH, SPST
$S_{_{_{2}}}$	SWITCH, SPDT
S ₃	SWITCH, 3-WAY
S ₄	SWITCH, 4-WAY
S _{os}	SWITCH, OCCUPANCY SENSOR-DUAL TECHNOLOGY
S _{MD}	SWITCH, OCCUPANCY SENSOR-MOTION DETECTOR
<u>@s&</u>	OCCUPANCY SENSOR, CEILING
S _{PC}	SWITCH, PHOTOCELL WITH REMOTE CONTROLLER
Sos	SWITCH, OCCUPANCY SENSOR-DUAL TECHNOLOGY
<u> </u>	FIRE ALARM STROBE
Œ	FIRE ALARM HORN/STROBE
<u>s</u>	FIRE ALARM SMOKE DETECTOR
θ	FIRE ALARM HEAT SENSOR
©	FIRE ALARM DUCT SMOKE DETECTOR
P	FIRE ALARM PULL STATION
DH	FIRE ALARM DOOR HOLD
<u> </u>	EXIT LIGHT FIXTURE
	EXIT LIGHT FIXTURE WITH DIRECTIONAL ARROW
	EMERGENCY LIGHT FIXTURE WITH EXIT SIGN
	EMERGENCY LIGHT FIXTURE
<u></u>	TELEPHONE/DATA OUTLET
▼	TELEPHONE OUTLET
<u> </u>	CEILING LIGHT OUTLET
Φ	WALL LIGHT OUTLET
	CIRCUIT HOMERUN
(E)	REPRESENTS EXISTING CONDITION















M2.0



4 3-D HATCHERY BUILDING NEW PLUMBING PLAN
M2.0 SCALE: NTS

KEYED PLUMBING NOTES

1) REMOVE ELBOW AND PREP FOR PIPING EXTENSION WITH

(2) ADD PIPING AND FITTINGS SHOWN IN BOLD. REDUCERS NOT SHOWN FOR CLARITY. USE CONCENTRIC

③ INSTALL NEW 6" WELL AND SPRING PIPING MAX 5' AFF.

(4) CUT CONCRETE FLOOR FOR NEW 6" PIPING INSTALLED BELOW GRADE.

(5) INSTALL NEW 6" WELL AND SPRING LINES UNDERGROUND TO NEW REARING ROOM A. BED PIPING WITH SAND, BRIDGE WITH GRAVEL AND COMPACT BACKFILL. 6' 6" MINIMUM BURY.

6 NEW 6" WELL AND SPRING LINES UP THROUGH FLOOR OF REARING ROOM A. SLEEVE PENETRATIONS THROUGH FLOOR WITH 5 GALLON BUCKETS. VALVE TO BE 3' AFF

7) FLOOR DRAIN IN HOT ROOM TO DRAIN INTO TROUGH IN REARING ROOM B.

MINIMUM.

8 TROUGHS IN REARING ROOMS A & B TO DRAIN INTO SUMP IN MECHANICAL ROOM.


9 UV DISINFECTION SYSTEM, SUMP PUMP, AND PIPING LOCATED IN MECHANICAL ROOM SUMP. SEE SUMP AND SUMP PUMP DETAILS ON M3.0.


10 6" DRAIN TO CONNECT TO 27" RCP DRAIN PIPE WITH NEW 48"Ø MANHOLE.


11) INSTALL SPRING PIPING SIMILAR (NOT SHOWN ON PLANS)
AS WELL PIPING. SLEEVE AND SEAL ALL WALL
PENETRATIONS WITH PVC AND 100% SILICONE. MOUNT
PIPING HORIZONTALLY 48" AFF.

12 MOUNT ALL INDOOR PIPING ON STRUT SECURED TO WALL AND CLAMPS.

13 VALVES TO BE APOLLO MODEL 215LxxSSP2FA1, OR EQUAL LUG STYLE VALVES. PROVIDE FLANGES AND BARE PVC CONNECTION ON OUTLET FOR FWP STAFF TO CONNECT OWNER PROVIDED CONNECTIONS.







NEW SUMP DRAIN PIPING DETAIL

√ M3.0

EMERGENCY SHUTDOWN VALVE (TYP)

MANUAL BUTTERFLY VALVE (TYP)

APOLLO MODEL WD14504SE10

CLOSE MOUNTING KIT- APOLLO MODEL CX03055

MOUNTING KIT- APOLLO MODEL CX03055


ACTUATOR-

OR EQUAL

VALVE -


APOLLO MODEL WD14504SE10

APOLLO MODEL LB0A8, 120V, 290lb-in, 5s



FROM SP-1 &

NEW SUMP PIPING DETAIL SECTION



2" DISCHARGE

CHECK VALVE (PVC)

9.5" MINIMUM SUBMERGENCE LEVEL

SUMP PUMP DETAIL SECTION

M3.0

M3.0

PLUMBING FIXTURE SCHEDULE PIPING CONNECTIONS FIXTURE TAG DESCRIPTION MANUFACTURER & MODEL # REMARKS TRAP S/W VENT C.W. H.W. FD-1 | FLOOR DRAIN | **ZURN ZN415BZ** 4''

GRILLE/REGISTER/DIFFUSER SCHEDULE								
SR	=SUPPLY DIFFUS	SER RG=RETURN GRIL	LE SD=SUPPLY DII	FFUSER EG	S=EXHAUST GRILLE	TG=TRANSFER GRILLE		
TAG NO.	NEXK SIZE	TYPE	MANUFACTURER	AND MODEL	MATL/FINISH	OPTIONS AND ACCESSORIES		
RG-1	10" X 10"	WALL MOUNT	NAILOR 71	45H-O	WHITE			
Notes:								
_								

EQUIPMENT	SERVICE	UNIT	WEIGHT	INPUT	El	ECTRIC	MANUFACTURER	
TAG	SERVICE	MODEL/SIZE	(LBS)	(KW) NOM	FLA	VOLTPHCY.	- MANUFACTURER	OPTIONS-ACCESSORIES
EH-1	HEATING	240-U1050D	<25	5	14.18	208/3/60	INDEECO	
EH-2	HEATING	240-U1038D	<25	3.8	10.85	208/3/60	INDEECO	
EH-3,4	HEATING	240-U1025C	<25	2.5	12.3	208/1/60	INDEECO	

				PUN	IP SCHEDULE				
ITEM TAG	ITEM TAC SEDVICE LOCATION				MOTOR		MANUFACTURER & MODEL	OPTIONS-ACCESSORIES	
ITEM TAG	SERVICE	LOCATION	HP	RPM	VOLTPH-CY.	FLA	WANDFACTORER & WODEL	OF HONG-ACCESSORIES	
P-1	SUMP PUMP	MECH ROOM SUMP	1/2	3450	115-1-60	8.5	LIBERTY 287	1	
NOTES:									
1. ORDER W	ITH 25' CORD LEN	NGTH (-2).							

				FAN SCHEDUL	E					
EQUIP. NUMBER	SERVICE	ACE LOCATION		STATIC PRESS		M	OTOR		MANUFACTURER & MODEL	NOTES
EQUIP. NUIVIDER	SERVICE	LOCATION	CFM	(IN W.G.)	AMP	WATTS SONES		VOLT/PH/CY	WANDFACTORER & MODEL	NOTES
EF-1	EXHAUST	HOT ROOM	50	0.25	0.53	45.1	2	120/1/60	GREENHECK SP-B70	1
EF-2	EXHAUST	REARING A	225	0.25	0.77	83.1	2.5	120/1/60	GREENHECK SP-A250	1
EF-3	EXHAUST	REARING B	154	0.25	1.3	113	2.5	120/1/60	GREENHECK SP-A190	1
RF-1	RADON	MECHANICAL ROOM	150	0.25	0.73	83	-	120/1/60	FANTECH DBF4XLT	2,3
Notes:										

1. OPERATE AS TASK EXHAUST AS CONTINOUS (MANUAL ON/OFF) WHEN ROOM IS ENGAGED WITH FISH.

2. OPERATE CONTINUOUSLY 24/7.

3. SUPPLY AND INSTALL TJERLAND MODEL RA1 FAN FAILURE ALARM TO SOUND AUDIBLE ALARM WHEN FAN FAILS.


PIPE MATERIAL AND INSTALLATION SCHEDULE								
SERVICE OR SYSTEM	MATERIAL	PIPE SIZE	INSULATION THICKNESS	PIPE SIZE	PRESSURE TEST*	NOTES:		
DOMESTIC COLD WATER	TYPE L COPPER, VIEGA PEX (INSIDE WALLS AND CRAWLSPACE ONLY), PRO-PRESS	ALL	1/2" FIBERGLASS	ALL	100 PSI AIR-30MIN	1,2		
DOMESTIC HOT WATER (100-180DEG F)	TYPE L COPPER, VIEGA PEX (INSIDE WALLS AND CRAWLSPACE ONLY), PRO-PRESS	ALL	1" FIBERGLASS	ALL	100 PSI AIR-30MIN	1,2		
SANITARY SEWER U/G	SCHEDULE 40 PVC DWW, HUBLESS CAST IRON	ALL	NONE	N/A	20 PSI AIR-60MIN			
SANITARY SEWER A/G	SCHEDULE 40 PVC DWW, HUBLESS CAST IRON	ALL	NONE	N/A	20 PSI AIR-60MIN	2		
HATCHERY PIPING	SCHEDULE 40 PVC DWW (PRESSURE) / SCHEDULE 80 SOLVENT WELD FITTINGS	ALL	NONE	N/A	25 PSI AIR-60MIN			
RADON PIPING U/G	SDR / PERFORATED	ALL	NONE	N/A	N/A			
RADON PIPING A/G	SCHEDULE 40 PVC	ALL	NONE	N/A	N/A			


1) INSULATION TO BE OF HEAVY DENSITY FIBERGLASS WITH ALL SERVICE JACKET (WHITE). FITTING TO BE PVC ZESTON COVERS WITH FLEXIBLE INSULATION WRAP. SEAL ALL JOINTS WITH SEALANT. K VALUE NOT TO EXCEED 0.27 BTU PER IN/h*FT^2 DEG F.


2) SEISMIC BRACE ALL PIPE GREATER THAN 2 1/2" ID PER LOCAL CODE.

GENERAL NOTE: SEAL ALL NON TRATED STRUCTURE PIPE PENETRATIONS INCLUDING DRAFT SHOPS WITH SILICON OR FIRE RATED EXPANDING FOAM. SEAL ALL RATED PIPE PENETRATIONS IN ACCORDANCE WITH CONTRACTOR SELECTED MFR FIRE CAULK SYSTEM (AND OR FIRE COLLAR) AND MATCH RATING WITH SPECIFIC UL LISTING. PROVIDE ENGINEER AND INSPECTOR FOR AHJ WITH SHOP.

* PROVIDE WRITTEN AND SIGNED REPORT BY CONTRACTOR FOR ALL SYSTEMS TESTED, TYPE OF TEST, DATE, PRESSURE, TIME START, TIME END AND SYSTEM TESTED. SUBMIT TO ENGINEER IN IOM SUBMITTAL.







REBID SET

Dawes Engineering & Design

ADDITION

(406) 441-4000 p

ISSUE DATE:

DATE: JULY 17, 2017

DRAWN BY: PM/WW

CHECKED BY: RD

REV #: X REV DATE: XX/XX/XXX

E1.0

GENERAL LIGHTING NOTE

REARING ROOM A

REARING

ROOM B


NEW LIGHTING FLOOR PLAN

PANEL D

REARING AND HOT ROOM LIGHTING TO BE MANUALLY

CONTROLLED BY FWP OPERATORS TO PROVIDE BEST QUALITY DESIRED LIGHTING LEVEL TO CONTAINED FISH

							PA	NEL N	/IDB (E	XISTI	NG)							
PANEL LOCATION: WASHOE HATCHERY					L	-L VOLT:	208	PHASE: 3		MAIN: BREAKER Y			BREAKER N					
MFR/MODEL: SQUARE D-NQ				L-N VOLT:		120	WIRES: 4					FED FROM:			MDP			
AIC: 10,000			AMP:		600	NEURAL 100%		COND. SIZE: (EXIST)				M	OUNT:	RECESSED				
BREAKER						T/S/O/M/	PHASE		T/S/O/M				BREAKER		R			
DESCRIPTION	TYPE	POLE	AMP	L-LOAD	R-LOAD	O-LOAD		ļ	PHASE				R-LOAD	L-LOAD	AMP	POLE	TYPE	DESCRIPTION
PROVISION		3	100					1	Α	2					100	3		PANEL C (EXIST)
								3	В	4								
								5	С	6								
PROVISION		3	100					7	Α	8					100	3		PANEL D (NEW)
								9	В	10								_
								11	С	12								
PROVISION		2	200					13	Α	14					200	3		PROVISION
								15	В	16								
								17	С	18								
PANEL B (EXIST)		2	200					19	Α	20					200	3		PANEL A (EXIST)
								21	В	22								
								23	С	24								
								25	Α	26								
								27	В	28								
								29	С	30								
								31	Α	32								
								33	В	34								
								35	С	36								
								37	Α	38								
								39	В	40								
								41	С	42								
							M				M							
							A				A							
A. II. M. 1. T. 1. A. C. 1. 1.				_	_		S				S		_			0111111	. D. /	NINESTEE : S . S .
SUMMARY CONNECTED LOADS 0			0			E LOAD			E		0	0		SUMM	ARY CO	DNNECTED LOADS		
							H (VOLT-AMPERES)			H								
							T				T							
							0				0							




UV EQUIPMENT SCHEDULE ELECTRICAL ENCLOSURE									$\overline{}$
ITEM TAG	MANUFACTURER AND MODEL #	LAMPS	INPUT WATTS	UV-C OUTPUT WATTS	MAX AMPS 120V/230V	MAX PSI		MIN GPM	NOTES
UV-1,2	PENTAIR SVP402060B11	2	260	80	3.9/2.0	50	112	18	1
NOTES:			SE. NEMA 4 ENC	l	0.0.2.0				

LIGHT FIXTURE SCHEDULE												
DESIGNATIO		LAMP		TOTAL	NOTES							
N LETTER	MANUFACTURER	DESCRIPTION	CATALOG NUMBER	LOCATION	OCATION MOUNTING		NUMBER	WATTS	NOTES			
Α	LITHONIA LIGHTING	LOW-PROFILE LED WRAP	LBL4 4800LM 80CRI 40K MIN1 ZT MVOLT	CEILING	SURFACE	LED	1	40.8	2,3			
В	LITHONIA LIGHTING	LED EXTERIOR WALL PACK	CSXW LED 30C 700 40K TFTM MVOLT DDBXD	WALL	SURFACE	LED	30	104	1			
NOTES:												
1) DAYLIGHT SENSOR (FACTORY INSTALLED).												

3) PROVIDE CONTROL TO BE LEVITON (OR EQUAL) MANUAL SWITCH WITH 0-10V DC LEVER CONTROL.

PANEL "D" PANEL LOCATION: WASHOE HATCHERY L-L VOLT: 208 PHASE: 3 BREAKER Y MFR/MODEL: SQUARE D-NQ L-N VOLT: 120 WIRES: 4 WIRE SIZE: 4-#2/0 THW FED FROM: MDP MOUNT: SURFACE AIC: 10,000 AMP: 125 NEURAL 100% COND. SIZE: 3" BREAKER **BREAKER** T/S/O/M/ PHASE YPE POLE AMP L-LOAD R-LOAD O-LOAD A/E/H /A/E/H O-LOAD R-LOAD L-LOAD AMP POLE TYPE DESCRIPTION DESCRIPTION INTERIOR LIGHTING 1 20 832 720 20 1 GFCI REARING ROOM A EAST RECEPTACLES 1 A 2 EXTERIOR LIGHTING 1 20 416 3 B 4 720 20 1 GFCI REARING ROOM A WEST RECEPTACLES PUMP (P-1) 1 20 978 M 5 C 6 360 20 1 GFCI MECHANICAL ROOM RECEPTACLES 2 20 2554 H 7 A 8 360 20 1 GFCI HOT ROOM RECEPTACLES **REARIMG ROOM A (EH-1** 720 20 1 GFCI REARING ROOM B EAST RECEPTACLES 2 20 2554 H 9 B 10 20 1 GFCI REARING ROOM B WEST RECEPTACLES 1954 H 11 C 12 720 2 20 REARING ROOM B (EH-2 20 1 GFCI EXTERIOR GFI OUTLET RECEPTACLES H 13 A 14 2 20 360 HOT ROOM (EH-3) H 15 B 16 E HOT ROOM (EF-1) 1 20 2559 45 20 1 H 17 C 18 E 83 REARING ROOM A (EF-2) MECH ROOM (EH-4) 1 20 2559 20 1 1 20 19 A 20 E UV LIGHT (UV-1) 20 1 REARING ROOM B (EF-3) 480 113 1 20 21 B 22 E 20 1 RADON FAN (RF-1) 83 1 20 23 C 24 E 20 1 GFCI UV ALARM CONTROL UV LIGHT (UV-2) 480 SPARE 1 20 25 A 26 20 1 SPARE SPARE 1 20 27 B 28 SPARE 20 1 SPARE 1 20 SPARE 29 C 30 20 1 SPARE 1 20 31 A 32 SPARE 20 1 SPARE SPARE 1 20 33 B 34 20 1 SPARE SPARE 1 20 35 C 36 20 1 SPARE SPARE 1 20 37 A 38 20 1 SPARE 1 20 SPARE 39 B 40 20 1 SPARE SPARE 1 20 41 C 42 20 1 978 SUMMARY CONNECTED LOADS 2208 LOAD 574 3960 SUMMARY CONNECTED LOADS (VOLT-AMPERES) 14134 0 0 **DESCRIPTION** CONN. KVA LEGEND/KEY DEM. KVA T=TRANSFORMER 2.2 2.8 TOTAL CONNECTED LOAD 21.3 KVA LIGHTING 1.25 59.1 AMP TOTAL DEMAND LOAD RECEPTACLES (FIRST 10KW) S=SUBFEED 4.0 61.4 AMP 22.1 KVA 1.0 RECEPTACLES (REMAINDER) 0.0 0.5 DESIGN (MAX) 100 AMP 72 KVA O=OTHER MOTORS 0.0 1.0 SPARE LOAD 39 AMP 49.9 KVA M=MOTOR LARGEST MOTOR A=APPLIANCE 1.0 1.25 1.2 APPLIANCES 0.0 1.0 E=EQUIPMENT CONNECTED LOAD BALANCE SUMMARY SUBFEED PHASE A H-HEATING 0.0 7.373 KVA 0.8 0.0 20.5 AMP **EQUIPMENT** 19.7 AMP 7.097 KVA R=RECEPTACLES 1.0 PHASE B **HEATING** PHASE C 20.5 AMP 1.0 7.384 KVA L=LIGHTING 14.1 14.1 TRANSFORMER CONN.=CONNECTED 0.0 1.0 DEM.=DEMAND 0.0 1.0 0.0 4 % OTHER A TO B B TO C -4 % SPR=SPARE 22.1 KVA C TO A 0 % SPC=SPACE TOTAL KVA 21.3 KVA TOTAL AMP 61.4 AMP D.F.=DEMAND FACTOR 59.1 AMP 200 AMP GFCI=GROUND FAULT CIRCUIT DESIGN (MAX) SPARE 138.6 AMP ST-SHUNT TRIP



2) 0-10V DC DIMMING